


# EB-125 Series


Retractable Injector 150psi Rated w/Check Valve and QR Coupler

3/4" Main Connection x 3/8" Solution Tube



\*Brass Valve/Compression Assembly shown, Stainless Steel also available, see ordering options below.

### Flexible Hose Assemblies



### Tip Configurations



## Ordering Information

**Sample Part Number: EB-125-B-P-(Specify)-0-V**

Series	Valve/Compression Material	Solution Tube Material	Insertion Length	Tip Configuration	Check Valve Seal Type	Flexible Hose Assembly
EB-125	B = Brass S = Stainless Steel	P = PVC S = Stainless Steel H = HASTELLOY® C-276 A = Alloy20 T = Titanium G2	(Specify) Note: PVC, CPVC, models have a maximum warranted insertion length of 6 inches. Consult factory for lengths greater than 6 inches.	O = Standard B = 45° Bevel CV = Saf-T-Seal Viton CE = Saf-T-Seal EPDM DH = Diffuser Holes	V = Viton E = EPDM	See Flexible Hose Assembly Product Page For Ordering Options.

CA and VT compliant NO-LEAD brass main connections are available. Indicate "-NL" at the end of the model number.

## Technical Notes

- PVC Solution Tubes are Schedule 80 pipe with an O.D. of 0.675 inches and an average I.D. of 0.403 inches.
- Alloy Solution Tubes are Schedule 40 pipe with an O.D. of 0.675 inches and an average I.D. of 0.473 inches. Schedule 80 Alloy Solution Tubes are available upon request - consult factory for details.
- Saf-T-Flo does not recommend nor warranty PVC/CPVC Solution Tubes where velocities in the process main exceed 6 fps.
- Main Connection and Inlet Connection are NPT by default. AWWA and BSP thread options are available. Consult factory for details.
- Check Valve and QR Coupler are PVC.

HASTELLOY® is a registered trademark of Haynes International, Inc.